

AMENDMENTS TO THE SPECIFICATION

Please amend the specification at the paragraphs listed below wherein paragraph numbering corresponds to the numbering as published in US 2007/0128442.

[0039] The above object is solved by ~~the materials~~
~~composites of~~ a moulded article ~~of~~ comprising at least one
transparent or translucent dyeable plastics moulding compound
layer ~~which moulded article is~~ bonded to at least one
transparent or translucent surface layer and/or to decorative
films, functional films or coats or rubbers or other plastics,
~~characterised in that said plastics moulding compound used for~~
~~the manufacture of said moulded article,~~ wherein said surface
layer ~~or said other plastics~~ contains in an amount of 0.01 to
5.0% by weight, preferably 0.01 to 2.0% by weight, ~~each~~
~~related to the total weight of the moulding compound,~~ at least
one lubricant ~~selected from the group consisting of sorbitan~~
~~esters, sebacic acid esters, dodecanedioic acid esters,~~
~~docosanoic acid esters, glycerine, glycol, diethylene glycol,~~
~~stearoyl amide, stearyl stearate, ethylene bisstearoyl amide,~~
~~octane pyrrolidone, and from the group consisting of non-polar~~
comprising paraffin oils and 2,6,10,15,19,23-hexamethyl
tetracosane or an isomer of 2,6,10,15,19,23-hexamethyl
tetracosanes, ~~and that a permanent adhesion to said other~~

~~plastics layers and/or films or coats or rubbers or other~~
~~plastics is achieved (cf. claim 1).~~